



Brilliantline Dichroic

Brilliantline Dichroic 20W GU5.3 12V MR16 10D 1CT

Low-voltage, xenon gas-filled halogen burner with axial filament optically positioned in a glass reflector

Product data

• Product Data

Order code	424549 60
Full product code	871150042454960
Full product name	Brilliantline Dichroic 20W GU5.3 12V MR16 10D 1CT
Order product name	Brilliantline Dichroic 20W GU5.3 12V MR16 10D 1CT
Pieces per pack	1
Packing configuration	10X5F
Packs per outerbox	50
Bar code on pack - EAN1	8711500424549
Bar code on intermediate packing - EAN2	8711500424655
Bar code on outerbox - EAN3	8711500424709
Logistic code(s) - 12NC	924050017101
ILCOS code	HRGS-20-12-GU5.3-50/10
Net weight per piece	30.000 gr

• General Characteristics

Philips Code	14610
ANSI Code Halogen	ESX
Cap-Base	GU5.3
Bulb	MR16 [MR 16inch/50mm]
Bulb Finish	Clear
Operating Position	any [Any or Universal (U)]
Life to 50% failures	4000 hr

• Electrical Characteristics

Lamp Wattage	20 W
Lamp Wattage Technical	20.0 W
Voltage	12 V
Lamp Current	1.73 A
Dimmable	Yes

• Light Technical Characteristics

Beam Angle	10 D
Beam Angle Technical	10 D
Luminous Intensity	5000 cd
Color Rendering Index	100 Ra8
Color Temperature	3000 K
Color Temperature Technical	3000 K

• Product Dimensions


Overall Length C	46 mm
Diameter D	50 mm

• Luminaire Design Requirements

Cap-Base Temperature	350 C
Bulb Temperature	250 C

PHILIPS
sense and simplicity

Dimensional drawing



Product	C (Max)	D (Max)
DICHRO Pro 14610 20W GU5.3 12V MR16 10D	46	51

